

Light Stand 250 cm - Levelling Leg

Reference: SBX-BSTAND250BLL



- Payload: 3 Kg
- Max height: 250 cm | Min height: 76 cm
- Material: aluminum
- Levelling leg
- Air-cushioned
- 16 mm dual mounting spigot (5/8" stud)



Product description:

Compact three risers light stand designed to support small lighting fixtures equipped with 16 mm (5/8") receiver.

Featuring a levelling leg for balancing, this stand can be used on uneven surfaces like stairs or rough terrain

The stand rises to a maximum height of 250 cm, folds down to 76 cm and can support lighting fixtures or other studio accessories up to 3 kg weight.

Includes a removable 16 mm (5/8") spigot ended with 1/4" & 3/8" threads. The spigot is installed in a dual position top end receiver allowing for a light head to be mounted vertically or angled at 90°. This feature is specially handy for those light fixtures that have a limited tilting down capability due to yoke bar position.

Air-cushioned collapsing protection ensures a safe operation when slowly lowering the gear during height adjustments.

The column and legs are made of aluminum alloy, making it lightweight to be carried on location, while the structural elements are made of metal alloy for increased strength and durability for years in service.

The black anodized finish of the stand eliminates any unwanted reflections, making it suitable for studio applications.

*NB: The maximum payload is rated for the stand columns half-extended.

Technical Specifications:

Stands

Stand type:	Baby stand
Mounting	Stud 16mm (5/8") with 1/4" top screw
Maximum height	250 cm
Minimum height	76 cm
Maximum payload	3 kg
Folded length	76 cm
Footprint diameter	94 cm
No of sections	4
Column diameters	19 / 22 / 25 / 30 mm
Legs diameter	22 mm
Leveling leg	Yes
Collapsing protection	Air cushioned
Material	Aluminum
Color	Black
Weight	1.85 kg