

# Cinelight X-60/90 HMI Flood Light

Reference: LHL-X6090KIT



- Dual wattage head 6000W / 9000W
- Electronic Ballast 1Khz flicker free
- Dual-wattage ballast 6000/9000
- Hot-restrike, PFC
- DMX512 ballast control option
- Wide beam angle up to 125°



## Product description:

Company - **S.C. CINEART S.R.L.**

Address - Ion Ionescu de la Brad 28, 610209, Piatra Neamt, Romania  
VAT No - 22380512 | REG No. J27/1210/100

email: sales@cinelight.com  
web: www.cinelight.com

All rights reserved. Use without permission is prohibited. © 2019 CINEART SRL

## Technical Specifications:

## HMI - Fixture

Beam type	flood
Rated power	9000 watts
Lamp type	HMI
Lamp socket	GX38
Color temperature	6000K
Beam angle	125°
Lens type	Clear
Lens size	536 x 490 mm
Filter slot size	518 mm
Barndoors slot size	518 mm
Yoke mount	Spigot 28mm pin
Housing color	Gray & blue
Housing material	Aluminum
Lamp head dimensions	77 x 70 x 32
Lamp head weight	37 kg

## HMI - Ballast

Ballast power	9000 watts
Ballast line power	11200 VA
Ballast nominal current	56-44A
Ballast operation voltage	190-245 VAC
Ballast frequency	50-60 Hz
Ballast current characteristics	Square wave, 75Hz
Ballast power factor	0.98
Ballast dimming range	100%-50%
Ballast starting	Hot & cold restrike
DMX control	Optional
DMX connectors type	XLR-5P
ballast power cable length	7.5 m
Power cord total length	3.5 m
Ballast dimensions	49 x 27.5 x 36.5 cm
Ballast weight	30 kg
Ballast protection class	IP32