

# Stand with Boom Arm, Pivot Clamp & Counterweight

Reference: SBX-BOOMARMPIVS



- Telescopic boom arm: 116 to 216 cm
- Stand maximum height: 190 cm
- Pivoting clamp supporting diameter: 30 mm
- Packed length: 120
- Material: aluminum with black finish



## Product description:

Boom Stand Set includes 2-section boom arm with counterweight, 2-riser aluminum stand with pivoting clamp and stand wheels. All the components can be used individually or assembled together.

A boom arm is ideal for lighting a subject from above, or to create more freedom of action for the photo or videographer. With a boom arm you can hang your studio lighting above your subject, without it being visible in the picture/video. You also create more freedom by walk under the lighting, for example.

The pivoting clamp is suitable for 30 mm diameter boom arms and features an "L" pull & twist mechanism for increased torque and faster tightening. With the help of the pivoting clamp, the boom arm can be easily adjusted, even when loaded with a lighting fixture.

For greater stability of the boom arm, a red painted iron weight is used as a counter balance. It features a long locking handle that tightens the rubberized grip on the boom arm.

The stand wheels are used to increase the mobility around the studio of the light boom assembly, even when the boom is loaded.

### Product features:

Weight: 9.2 kg  
Stand type:: Baby stand  
Mounting: Stud 16mm (5/8") & Receiver 28mm (1-1/8")  
Maximum height: 190 cm  
Minimum height: 88 cm  
Folded length: 90 cm  
No of sections: 2  
Footprint diameter: 100 cm  
Column diameters : 25 / 30 mm  
Legs diameter: 22 mm  
Leveling leg: No  
Maximum payload : N/A  
Collapsing protection: Spring  
Material: Aluminum  
Color: Black  
Includes boom arm: Yes, 116-216 cm