

# Tube LED Ultra Soft Bi-Color

Reference: LLP-TUBELEDUSBIC



- Power: 16W
- Light output: 2900lx @ 1m
- Color temperature: 3000K-5600K | CRI 97 TLCI 98
- Size & weight: 60 x 6 x 6 cm | 950 g
- Ultra soft light with wide beam & smooth shadows
- Saber design, compact & lightweight
- Multiple 1/4" mounting threads for easy gripping
- Optional accessories: handle, radio remote



## Product description:

The Cinelight Tube-LED Ultra Soft is a highly portable LED light designed for photo and video applications. The fixture consists of an array of SMD LED's under a dense diffusion cover which output an ultra soft light with wide beam and smooth shadows . The fixture design resembles the look of a common-classic 2FT / 60cm fluorescent tube lamp making it familiar for all gaffers. Being lightweight and compact makes it suitable for confined spaces where heavy lights along with matching stands and accessories are not the best option to use.

Continuous adjustable brightness and color temperature

The Tube-LED Ultra Soft is fully dimmable, having adjustable brightness from 10% to 100% using the dedicated

knob on the back. Also, the color temperature can be continuously adjusted from 3000K (warm tungsten) to 5600K (cold daylight). Due to the color temperature range, the Tube-LED can be used in mixed setups that include various lighting sources like fluorescent, tungsten, HMI, even flash lights.

No compromise for having a bi-color function!: thanks! to the new 2in1 SMD chip design the Bi-Color fixtures now output the same amount of light as a daylight only version.

#### Lightweight aluminum housing with built-in dense diffusion filter

The Tube-LED Ultra Soft comes with a built-in dense diffusion filter into a lightweight but solid aluminum housing. The fixture can be placed very close to the subject, wrapping it around in a soft light, with almost no heat generation.

#### Built-in 24Wh internal Li-Ion battery

The Tube-LED is powered via an internal 24Wh battery that features the latest Lithium-Ion technology and can be charged anywhere using the universal battery charger. The run time when fully charged can reach over 90 minutes at full brightness.

#### Inter linked design

A connector bracket is included in the package which can be used to join head-to-head two or more Tube-LED's to form a single long light source. This is a very useful accessory when there is a need for a wider Tube-LED like in full body photography.

#### Optional handle to hold the lamphead

The Tube-LED can be handheld by using the optional handle, providing an overall design of a saber from the well-known famous movies. Equipped with 1/4" mounting threads on both ends and another two on the back, the fixture can be easily gripped to most studio accessories like booms, clamps, hangers or stands.

#### Optional radio remote controller with large display

Brightness and color temperature values can now be adjusted from up to 50m distance using the optional 2.4Gh wireless remote. The remote controller features a large touch display for convenient operation. Remote controlling is available for one or more Tube-LED fixtures at once configured on any of the four assignable channels. This feature is very useful when an entire set needs to be adjusted at once or there is a need to turn off all the panels with a single command. With the same remote other fixtures like CineFLEX or SoftLED lights can be controlled.

#### Included transport bag

The Tube-LED Ultra Soft comes with transport bag with customized foam interior that holds and protects the lighting

fixture along with the included battery charger and the connection bracket.

#### Key Features:

- ultra-soft light output
- saber design of the LED light
- variable color temperature: 3000K -5600K with no light loss
- dimmable light intensity 100%-10%
- 24Wh internal Li-Ion battery
- aluminum & PVC housing
- multiple ¼" mounting threads for easy gripping

#### Product features:

Rated power: 16 watts  
Beam type: flood  
LED type: Bi-Color  
Voltage input: 12V  
Color temperature: 3200K-5600K  
CRI rating: 97  
TLCI rating: 98  
Beam angle: 60°  
Photometrics : 1m: 290 lx  
Dimming range: 100%-10%  
Battery mount: N/A  
Cooling system: Passive  
Power source: External, AC 100-240V 50 / 60 HZ  
Power connector type: CEE 7/7  
Power cord total length: 2.0 m  
Local functions control: Analog  
DMX control: No  
DMX connectors type: N/A  
WIFI control : No  
Remote control : Yes  
Yoke mount: N/A  
Housing material: Aluminum  
Housing color: Silver  
Lamp head weight: 0.95 kg  
Lamp head dimensions: 60 x 6 x 6 cm