

# C-150 Swiveling Pipe Clamp 28 & 16 mm

Reference: GCX-SWPIPECL150



- Fits on 28 to 78 mm diameters
- For hanging on pipes or truss systems
- Easy pan fixtures by swivel function
- Combo mount: 28 mm & 16 mm
- Baby 5/8" pin (16 mm spigot & receiver)
- Junior 1 1/8" (28 mm) receiver
- Size: 32 x 20 x 7.5 cm | 1.90 Kg
- Payload: 50 Kg
- As: C150, KCP-150



## Product description:

Heavy duty C150 C-Clamp with swiveling Junior 28mm receiver designed to mount studio lighting fixtures on trusses and grid pipes with a diameter between 28 and 78 mm.

The structure is very solid and robust, made from gravity die casting aluminum ensuring better mechanical properties and a better quality of the product comparing to classic sand casting grip tools.

The clamp allows for mounting both small and large, heavy fixtures having two different attachment sizes: Baby 5/8" (16 mm) spigot & receiver and Junior 1-1/8" (28 mm) receiver.

The swiveling system allows for easy orientation of the hanged fixture without going through the trouble of loosening it from the mount. The swivel system is also equipped with a lock into position mechanism.

This clamp also features a cable lock to secure the junior 28 mm pin of the fixture when mounted and prevent an accidental loosening.

The load capacity of the clamp is up 10 Kg on the baby 5/8" (16 mm) attachment and up to 50 Kg on the junior 1-1/8" (28 mm) attachment.

Similar with other brands clamps: C150 swiveling C-clamp, KCP-150 Swiveling Pipe C Clamp w/ Universal Head.

Clamp weight: 1.90 Kg

## Technical Specifications:

## Grip &amp; Mounting

Grip type	Clamp
Mounting	Receiver 28mm & Stud 16mm
Openings	28-78 mm
Max opening	78 mm
Maximum payload	50 kg
Overall size	32 x 20 x 7.5 cm
Color	Black
Material	Steel alloy
Weight	1.9 kg