

Pro Clamp with Adjustable Handle

Reference: GCX-SUPERCLAMP



- Opens up to 60 mm
- Aka Super Clamp or Convi Clamp
- Adjustable pull & twist locking handle
- Spigot receiver with secure lock
- Spigot 16 mm with 1/4" and 3/8" threads included
- Can be used on pipes, trusses and flat surfaces
- Rubber-lined jaws
- Size: 9.5 x 5.5 x 13.5 cm | 0.45 kg
- Payload: 15 Kg
- As: 035, KCP-710B / KG701611, LS.035



Product description:

Strong, versatile mounting clamp, also known as Super Clamp or Convi Clamp.

A cammed screw mechanism closes and opens the rubber-lined jaws.

It can attach to round surfaces and flat surfaces from 10 mm to 60 mm width.

The baby pin snaps into place with a spring-loaded lock.

The locking handle features an "L" pull & twist (ratchet) design for increased torque and faster tightening.

The clamp body and locking handle are metal made.

The maximum recommended payload is 15 kg.

Includes a 16 mm spigot adapter with dual thread: 1/4" & 3/8" and saddle triangle wedge that presses into the jaw of any Pro Clamp to enable the clamp to be mounted securely on flat surfaces.

Ideal clamp for Cinema, Broadcast Lighting & Entertainment applications.

Similar with other brands clamps: O35, KCP-710B / KG701611 Convi Clamp with Adjustable Handle, LS-O35 Super clamp, CC-106R

Technical Specifications:

Grip & Mounting

Grip type	Clamp
Mounting	Stud & Receiver 16mm (5/8")
Openings	10-60 mm
Maximum payload	15 kg
Overall size	9.5 x 5.5 x 13.5 cm
Color	Black
Material	Steel alloy
Weight	0.45 kg