

KIT 3 x CineLED EVO "S" - 5600K

Reference: LLK-3xEVOSDY



- 3 x CineLED EVO "S" 5600K
- 3 x Acrylic diffusion filter
- 1 x Transport case
- Optional: stands, barndoors, softboxes, batteries



Product description:

Product features:

Rated power: 38 watts
Beam type: semi-flood
LED type: Daylight only
Voltage input: 11-16V

Color temperature: 5600K
CRI rating: 95
TLCI rating: 95
Beam angle: 45°
Photometrics : 1m: 4800 lx | 2m: 1250 lx | 3m: 550 lx
LED no: 576
Dimming range: 100%-0%
Display type: Simple - Monochrome
Battery mount: NP-F
Plug in connector type: Barrel 2.5 mm - female
LED surface dimensions : 19 x 19 cm
Cooling system: Passive
Power source: External, AC 100-240V 50 / 60 HZ
Power connector type: CEE 7/7
Power cord total length: 3.0 m
Local functions control: Analog
DMX control: No
DMX connectors type: N/A
WIFI control : No
Remote control : Yes
Yoke mount: Spigot 16mm receiver
Housing material: Aluminum
Housing color: Gray & black
Lamp head weight: 1.0 kg
Lamp head dimensions: 30 x 30 x 4.5 cm
No of heads: 3
KIT case size: 32 x 45 x 43 cm
KIT include stands?: Optional
KIT heads type: Flood lights
KIT total power: 114 watts