

# Maxi Brute Four Light 4000 watts

Reference: LTO-MAXIBRUT4KW



- Power: 1000W - 4000W max
- Voltage: 100V-250V compatible
- Lamp socket: Mogul end prong PAR 64
- Power plug: CEE Norm 2P+E type 32 / 32A-6H 200V-250V
- Weight: 10 kg
- 4 toggle switches allow total control over light output
- Focusing and light output vary by bulb type



## Product description:

The Cinelight MaxiBrute Four-Light 4KW is mainly used for lighting large areas in television and film productions.

The high intensity output of this fixture allows a minimum number of units for the required lighting level.

## Key Features:

- accepts different bulbs with built-in reflectors that disperse or intensify the light beam emitted from the heads

- may be used as a hanging, grid or pipe mounted fixture, or mounted on a combo / senior stand
- pivoted three globe modules for variable beam coverage
- four toggle switches allow total control over light output
- power: 1000W - 4000W max
- socket (lampholder): Mogul end prong PAR 64
- power plug type: 2P+E type 64 / 63A-6H 200V-250V
- focusing and light output vary by type of bulb used
- mounting: spigot 28mm pin

### Product features:

Rated power: 4000 watts

Beam type: flood

Voltage input: 100-240V 50 / 60 Hz

Color temperature: 3200K

Beam angle: According to lamp model

Photometrics : According to lamp model

Power connector type: CEE 2P+E

Power cord total length: 7.0 m

Yoke mount: Spigot 28mm pin

Housing material: Metal

Housing color: Black

Lamp type: PAR64

Lamp socket: GX16D

Lamp head weight: 10 kg

Lamp head dimensions: 65 x 62 x 24 cm