

CineFlo 4FT 4Bank - select

Reference: LFP-CINEFLO4F4B



- Power: 300W
- Lamp type: G13 KinoFlo True Match T12 75W
- Lamp control: Analog ON/OFF - four switches
- Size & weight: 130 x 33 x 7.5 cm | 5.2 kg
- External flicker free 4 bank - select ballast
- Detachable harness with color labeled lamp cables
- Lightweight polypropylene housing with reinforced ends



Product description:

Flicker-free fluorescent soft light source

The CineFlo lighting fixture is one of the most common fluorescent light used on big productions studios, in still photography and movie pictures. This flicker-free soft light source is the perfect choice for "infinity" white cycloramas and chromakey (blue/green screen) lighting. With its narrow profile and size, the CineFlo could deliver the quality of bounced light

sources without compromising any space on the set. All the components and accessories are fully compatible with the Kino Flo brand.

Lightweight polypropylene housing with detachable wiring harness

Designed with flexibility in mind, the tubes, wiring harness, and reflector can be quickly stripped out of the housing and employed in any number of configurations as needed. The whole lamphead is lightweight enough to be taped to a wall. The housing is made from polypropylene and has reinforced ends, to withstand intensive everyday use on busy sets.

Built-in barndoors and detachable louver

To control the light emitted by the CineFlo, the built-in barndoors can be used to narrow the beam angle and the detachable louver to reduce the intensity. Also, the barndoors, when closed, protect the lamps during shipping and handling.

Daylight and tungsten balanced fluorescent tubes

To adapt to different shooting conditions, both tungsten (5600K) and daylight (3200K) fluorescent lamps can be used. Each lamp can be individually switched on and off to obtain the desired output from the fixture. The detachable lamp harness has 4 different individual cables, shorten to the length and color labeled to easily match each lamp separately, without any hassle or confusion generated along the process.

Professional high frequency ballast

The ballast is manufactured from high quality components, matching the increased performance and durability of higher cost competitors. The ballast is designed to operate the lamps at 24'000 Hz, 400 times faster than traditional ballasts, ensuring a flicker-free operation at any shutter speed. Includes an easy to change power fuse to protect the ballast against electrical shocks.

The ballast has 4 separate switches to control each lamp individually and adjust the light output accordingly.

Our CineFlo 4Bank select ballast features an additional high-output/standard-output toggle switch. By using the high-output setting for 4FT (75W) lamps and the standard setting for 2FT (40W) lamps, the same ballast can work for both CineFlo 4FT and 2FT fixtures.

MTP-K41 twist-lock mounting plate

The omni-mount (MTP-K41) twist-lock plate and is an universal mount designed for single, double and 4 bank fixtures and up to 4ft size. The MTP-K41 features four capture points and a lock pin to secure it on the back of the CineFlo and mounts it on a 3/8" receiver. This mounting plate is designed to work with a grip head allowing placing the fixture in virtually any position. An optional baby-receiver mount (MTP-B41) is available to mount the CineFlo directly on top of a light stand.

Package Content:

- 1 x CineFlo 4FT 4Bank - select
- 1 x Reflector
- 1 x Detachable Harnesses
- 1 x Louver
- 1 x Omni mount MTP-K41
- 1 x 7m power cable
- 1 x External 4 bank ballast
- 1 x User manual

Technical Specifications:

Fluorescent - Fixture

Beam type	flood
Rated power	300 watts
Photometrics	1m: 2600 lx 2m: 780 lx 3m: 360 lx
Color temperature	3200K / 5600K
CRI rating	97
TLCI rating	97
Lamp type	F75/T12
Lamp socket	G13 Med BiPin
No of lamps	4
Dimming range	100% / 75% / 50% / 25%
Ballast type	External, 4 bank select
DMX control	No

Fluorescent - Powering

Rated power	300 watts
Voltage input	230V 50Hz
Ballast type	External, 4 bank select
No of ballasts	1
Ballast frequency	24000 Hz
Ballast power factor	98
Power connector type	CEE 7/4 - Schuko
Power cord total length	7.0 m

Fluorescent - Physical

Yoke mount	3/8" rod
Housing color	Black
Housing material	Plastic & Aluminum
Lamp head dimensions	130 x 33 x 7.5 cm
Lamp head weight	5.2 kg
Ballast dimensions	35 x 23 x 6 cm
Ballast weight	3.1 kg