

# CineLED EVO "S" - 5600K

Reference: LLP-CINELEDS5600K



- Power: 38W
- Light output: 4800lx @ 1m
- Color temperature: 5600K | CRI 95+ RA
- Size & weight: 30 x 30 x 4.5 cm | 1 Kg
- Lightweight aluminum housing with a slim profile
- Includes 2 acrylic filters: diffusion and warm
- Optional accessories: barndoors, softbox



## Product description:

The new CineLED EVO Series is the ultimate professional lighting solution for both studio and location work.

## Slim and lightweight body design

The newly redesigned slim profile is one of the best features of the CineLED EVO panels that

Company - **S.C. CINEART S.R.L.**

Address - Ion Ionescu de la Brad 28, 610209, Piatra Neamt, Romania  
VAT No - 22380512 | REG No. J27/1210/100

email: sales@cinelight.com  
web: www.cinelight.com

All rights reserved. Use without permission is prohibited. © 2019 CINEART SRL

truly distinguishes it among the wide variety of LED lights on the market. The lightweight aluminum housing with a sturdy structure and streamlined appearance certainly can overtake the conventional look of the most common LED fixtures. The CineLED EVO housing is also designed to dissipate the heat faster, increasing the led's life and maintaining the panel cool-to-touch. The fixture is equipped with a solid yoke bar with side locking "pull & twist" knobs, provided with dual mount spigot adapter (vertically and horizontally).

## Latest generation of performant LED's

The CineLED EVO "S" - 5600K features 576 high CRI (95+ RA) of new generation LEDs specially developed for photo-video applications where color accuracy is mandatory. The panel produces luminous, directional lighting, at a beam angle of 45 degree, drawing 38W while providing an output of a 650W tungsten light equivalent. The matrix layout of the LED bulbs facilitates a uniform blending of the color temperatures for a softer overall look. The CineLED EVO S can be used in studio setups as an edge (contouring) light, being powerful enough to act as key light as well.

## Intuitive & precise light adjustments

The output is dimmable from 100% to 0% with constant color temperature across the entire dimming range.

The digital display located on the back of the panel shows the brightness value so that multiple similar LED fixtures can be easily matched in the same setup.

## Common powering options

The unit can be powered via 2 Sony NP-F batteries, by one 14.8 V external battery using a D-Tap cable, or via the included AC/DC 12 V power adapter. A battery level button is located on the back of the panel that shows the charging level.

## Available light modifiers: acrylic filters, 4-leaf barndoors, softbox

The CineLED EVO S panel comes with two acrylic filter panels included: one translucent diffusing panel to soften the shadows and one warm filter that converts the color temperature of the led's so the CineLED EVO S can be used with tungsten lights.

The front housing includes 2 accessory slots for inserting the optional barndoors, softbox kit or 2 filter panels at the same time. The barndoors and the softbox can be each used along with the desired filter panel. These optional accessories increase the versatility in using the CineLED EVO panels.

## Transport bag included for easy storage and carrying

The CineLED EVO S 5600K comes with transport padded soft bag that fits inside the fixture

along with the filters and batteries. The bag is thick enough to offer some protection to the LED panel, being also an indispensable accessory for location assignments.

### Key Features:

- display showing brightness level adjustments
- accurate color rendering: CRI / TLCI 95+
- slim design (4.5 cm thickness)
- lightweight aluminum housing with sturdy structure
- power efficient, draws only 38W, 650W tungsten equivalent output
- dial-up brightness 100% - 0% with no color shift
- 2 slide-in accessory slots on the front housing
- battery operated (two NP-F mounts)
- battery level button to show charging level
- included two acrylic filter panels: diffusion and warm filter
- optional: metal barndoors, softbox

### Package Content:

1 x CineLED EVO S 5600K HO

1 x yoke bar with dual mount 5/8" receiver

1 x AC-DC power adapter

1 x power cable 3m

2 x acrylic filters (warm, diffusion)

1 x user manual

## Technical Specifications: