

Cinelight X-25/40 HMI Flood Light

Reference: LHL-X2540KIT



- Dual wattage head 2500W / 4000W
- Electronic Ballast 1Khz flicker free
- Dual-wattage ballast 2500/4000
- Hot-restrike, PFC
- DMX512 control ballast option
- Wide beam angle up to 125°



Product description:

Technical Specifications:

HMI - Fixture

Beam type	flood
Rated power	4000 watts
Lamp type	HMI
Lamp socket	G38
Color temperature	6000K
Beam angle	125°
Lens type	Clear
Lens size	400 x 393 mm
Filter slot size	422 mm
Barndoors slot size	426 mm
Yoke mount	Spigot 28mm pin
Housing color	Gray & blue
Housing material	Aluminum
Lamp head dimensions	54 x 90 x 32 cm
Lamp head weight	18 kg

HMI - Ballast

Ballast power	4000 watts
Ballast line power	4650 VA
Ballast nominal current	52-19A
Ballast operation voltage	180-235 VAC
Ballast frequency	50-60 Hz
Ballast current characteristics	Square wave, 75Hz
Ballast power factor	0.98
Ballast dimming range	100%-50%
Ballast starting	Hot & cold restrike
DMX control	Optional
DMX connectors type	XLR-5P
ballast power cable length	7.5 m
Power cord total length	3.5 m
Ballast dimensions	24 x 37 x 45 cm
Ballast weight	20 kg
Ballast protection class	IP32