

HMI MAX M18 Kit

Reference: LHP-MAX18KIT



- Dual-power: 1200W / 1800W
- MAX lens-less reflector
- HMI 6000K G38 metal-halide lamp
- Electronic Ballast 1KHz flicker free
- Multi-wattage ballast
575/800/1200/1800
- Includes barndoors and hard case.
- DMX512 control option



Product description:

Technical Specifications:

HMI - Fixture

Rated power	1800 watts
Lamp type	HMI
Lamp socket	G38
Color temperature	6000K
Beam angle	20°-60°
Lens type	MAX
Lens size	276 mm
Filter slot size	330 mm
Barndoors slot size	344 mm
Spot-Flood selector type	Mechanical
Yoke mount	Spigot 28mm pin
Housing color	Gray & blue
Housing material	Aluminum
Lamp head dimensions	68.5 x 38.5 x 45 cm
Lamp head weight	15 kg

HMI - Ballast

Ballast power	1800 watts
Ballast line power	1830 VA
Ballast nominal current	17-6A
Ballast operation voltage	90-265 VAC
Ballast frequency	50-60 Hz
Ballast current characteristics	Square wave, 75Hz
Ballast power factor	0.98
Ballast dimming range	100%-50%
Ballast starting	Hot & cold restrike
DMX control	Optional
DMX connectors type	XLR-5
ballast power cable length	7.5m
Power cord total length	3.5m
Ballast dimensions	20 x 28 x 36 cm
Ballast weight	10.5 kg
Ballast protection class	IP32